This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images, please do not report the images to the Image Problem Mailbox.



Figure 1a


First Local Area Network 37
33
34
BASE STATION
HOST COMPUTER
30
Second Local Area Network (Microlink Network) 41
MCD
35
36
MCD
Second Local Area Network (Microlink Network) 40
P
43
44
P
P
45
M C D = MOBILE COMPUTING DEVICE
P = PERIPHERAL DEVICE

Figure 1b


HOST COMPUTER
55
50
56
57
58
59
BASE STATION
BASE STATION
BASE STATION
BASE STATION
61
62
63
64
65
66
M C D
M C D
M C D
M C D
M C D
M C D
P
P
P
P
P
P
P
M C D = MOBILE COMPUTING DEVICE
P = PERIPHERAL DEVICE

Figure 1c


201
203
205
207
SYNC
Reservation Phase
Sessions
Optional TDMA Slots
200

Figure 2



Figure 3a



Figure 3b



Figure 4a



Figure 4b



Figure 5a



Figure 5b



Figure 6a



Figure 6b


SYNC
Res. Poll
RFP Addr 65
Sessions
Optional TDMA Slots
707
709
711
RR Poll Addr 65
Addr 65 Send First Packet
Poll Next
Addr 65 Send Second Packet
Poll Next
Addr 65 Send Third Packet EOD
Clear
[f r e e]
701
703
705
713

Figure 7a


SYNC
Res. Poll
RFP Addr 65
Sessions
Optional TDMA Slots
723
RR Poll RFP Addr 103
Addr 103 Poll CP
CP Send First Packet
Addr 103 Poll Next
CP Send Second Packet EOD
Addr 103 Clear
CP Clear
[f r e e]
721

Figure 7b



Figure 8



Figure 9a



Figure 9b


1001
1001
1001
1001
1001
1001
1001
Overlapping Base Coverage Areas
Areas Covered By Single Base

Figure 10



Figure 11


Base
Base
Base
1201
wireless link
Base
Base
1205
1203
Master
Slave
Building "A" LAN
Building "B" LAN
1207
1209

Figure 12


Base
Base
Base
1303
wireless link
1301
Wireless Base
Slave
Master
1305
Wired LAN
1307

Figure 13


1413
Portable Mobile Device
1401
1403
1405
1411
1409
Base
Base
Base
Wireless Base
LAN
1407

Figure 14


1503
1505
1509
SYNC
Res. Poll
Slot 1
Sessions
Optional TDMA Slots
Wired Base Station SYNC
Microlink Master SYNC
SYNC
Res. Poll
Slot 1
Sessions
1501
1507

Figure 15


Initial Acquisition Algorithm
Base Station Selected
Mobile Computing Device (MCD)
Registers with Appropriate
Base Station
MCD Monitors Communication
Link Quality, And Stores
Information Received From
HELLO Messages Such As Costs
of Connection And Frequency
Hop Sequences
Communication
Link Quality
Acceptable?
Yes
No
K
J
L

Figure 16a


K
J
L
Yes
Synchronization Attempted with Another Base Station, Selection Based on Lowest Cost of Connection
Any Untried Base Stations Left?
No
Synchronization Achieved?
No
Yes
New Communication Link Quality Monitored
Communication Link Quality Acceptable?
No
Yes
MCD Continues Monitoring Communication Link Until A HELLO Message is Received From the Base Station
Cost of Communication Link Acceptable?
No
Yes

Figure 16b


Initial Synchronization, Coordinate with Priority SYNC
Go To Sleep
Wake Up And Wait To Receive Next Priority SYNC
SYNC Recieved?
No
2 of Last 3 SYNC's Not Received?
Yes
Yes
No
2 of Last 3 SYNC's Have Poor Signals?
Yes
No
Stay Awake To Test Communication Link
Link Acceptable?
Yes
No
Execute Roaming Algorithm

Figure 17


Initial Synchronization, Coordinate with Priority SYNC
Sleep A Long Time (e.g., Seconds)
Wake Up Short Time (e.g., 500 µs) Before Expected Beginning Of Access Interval
Wait To Receive Next Priority SYNC
SYNC Received?
No
Yes
Link Acceptable?
No
Yes
Stay Awake To Test Communication Link
Link Acceptable?
Yes
No
Execute Roaming Algorithm

Figure 18


Transmit SYNC
Transmit HELLO (Optional)
Determine Extent Of Channel Traffic
Light Traffic?
Yes
n = 1
p < 1
No
Medium Traffic?
Yes
n > 1
p = 1
No
Heavy Traffic:
n > 1, p < 1
Transmit Reservation Poll, Including: n,p, Addresses With Pending Messages, Reserved IDMA
Receive Requests For Poll's (RFP's) From Devices In Reservation Slots
Reservation Resolution Poll:
Place Addresses of Identified Devices In Polling Queue, Transmit Poll To First Unit In Polling Queue. Polling Queue Order Is:
(1) Outbound Messages For Active Units
(2) Units Requesting a Poll In Previous Access Intervals
(3) Units Requesting A Poll In Current Access Interval
A

Figure 19a


A
Wait For Response To Poll (Data Fragment)
Response Received Within Timeout?
No
Addresses Remain In Polling Queue
Yes
Transmit Poll To Same Address
No
Near End Of Access Interval?
No
Response Indicate EOD (End-Of-Data) ?
Yes
Yes
D
C
E
F

Figure 19b-1


D
C
E
F
Yes
Polling Queue Empty ?
No
Yes
Near End Of Access Interval ?
No
Transmit Poll To Next Address
Yes
Near End Of Access Interval?
Yes
No
Control Point Device To Immediately Initiate Communication ?
Yes
No
Clear Message Transmitted, p ≠ o. (Explicit Idle Sense)
Clear Message Transmitted. p = o

Figure 19b-2


Transmit SYNC
Transmit HELLO (Optional)
Determine Extent of Channel Traffic
Light Traffic ?
Yes
n = 1
p < 1
No
Medium Traffic ?
Yes
n > 1
p = 1
No
Heavy Traffic:
n > 1, p < 1
Transmit Reservation Poll, Including: n,p, Addresses with Pending Messages, Reserved IDMA
Receive Requests for Poll's (RFP's) from Devices in Reservation Slots
Reservation Resolution Poll: Place Addresses of Identified Devices in Polling Queue, Transmit Poll to First Unit in Polling Queue. Polling Queue Order Is:
(1) Outbound Messages for Active Units
(2) Units Requesting a Poll in Previous Access Intervals
(3) Units Requesting a Poll in Current Access Interval
B

Fig. 20a


B
Wait To Receive Poll From Device
Poll Received Within Timeout?
No
Address Remains In Polling Queue
Yes
Send Data Fragment
End-Of-Data Fragment?
No
Yes
Wait For Clear Message From Device
G
H
I

Figure 20b-1


G
H
I
Device Address Removed From Polling Queue
Yes
Clear Message Received Within Timeout ?
No
Device Address Remains In Polling Queue
Near End Of Access Interval ?
No
More Outbound Messages ?
Yes
Transmit Request For Poll (RFP) To Next Device In Polling Queue
Yes
Transmit Clear Message, p = o
No
Polling Queue Empty ?
No
Continue Inbound Algorithm:
1) Transmit Poll
2) Wait For Response To Poll
Yes
Transmit Clear Message, p ≠ o.

Figure 20b-2


2100
SYNC
Res. Poll
Slots
RR
Poll Queue: Outbound and Slot Responses
Explicit/Implicit Idle Sense Access
Optional TDMA Slots
2101
2103
2113

Figure 21


SYNC
Optional TDMA Slots
Res. Poll
Slots
RR
Poll Queue
Explicit/Implicit Idle Sense Access
2201
2203
2207
2209
2200

Figure 22


SYNC
Res. Poll
Optional TDMA Slots
S l o t s
R R
Poll Queue
Explicit/Implicit Idle Sense Access
2301
2303
2305
2307
2309
2300

Figure 23


SYNC
Optional TDMA Slots
Poll Message Queue
Res. Poll
Slots
RR
Poll Inbound Message Queue or Explicit/Implicit Idle Sense Access
2401
2403
2405
2400

Figure 24

2500

2501

2503

2505

Preamble .....10101010101010101010101010101010101010101010101010101010101010.....		SYNC	Res. P II
Freq. Switching	Training and Acquisition	14 bytes	12 bytes
← 150 µsec →	← 300 µsec →	120 µs ++	110 µs ++

++ allows additional bit times for HDLC zero bit insertion

Figure 25

SYNC

2600

Byte	Content	Definition
1	FLAG	Frame Delimiter
2	Dest. Address 1	Destination Address (SYNC = Broadcast = $FFFF_H$)
3	Dest. Address 2	Destination Address, 2nd Byte
4	TYPE	Message Type=SYNC, Priority Sync, or Priority SYNC with HELLO
5	Source Address 1	Control Point Address
6	Source Address 2	Control Point Address, 2nd Byte
7*	SYSTEM ID	System Identifier (LAN ID)
8*	NET ID	Net ID
9*	Command/Status 1	Control Point Status
		2 Bits Control Point Type
		2 Bits Loading Factor
		1 Bit Scheduled Service Availability
		3 Bits Reserved
10*	Command/Status 2	Scheduled Services
		5 Bits Number of Allocated TDMA Time Slots
		3 Bits Number of Available Time Slots
11*	Random	Randomly Selected Character for Improved Encryption
12	CRC 1	Error Check
13	CRC 2	Error Check
14	FLAG	Frame Delimiter

Figure 26

*Optionally Encrypted Bytes

2700

Reservation Poll

Byte	Content	Definition
1	FLAG	Frame Delimiter
2	Dest. Address 1	Destination Address (RES = Broadcast = $FFFF_H$)
3	Dest. Address 2	Destination Address, 2nd Byte
4	TYPE	Message Type = RES POLL
5	SLOT PARMS	3 Bits Number of Slots
6		5 Bits Probability Factor
7*	Sequence	Hopping Sequence ID
8*	Index	Hopping Sequence Index
9*	NET PARMS	
		3 Bits Hop Rate
		2 Bits Al's per Hop
		3 Bits Reserved
10	CRC 1	Error Check
11	CRC 2	Error Check
12	FLAG	Frame Delimiter

Figure 27



Fig. 28A



Fig. 28b



Figure 28C



Fig. 29A


WAN
Link
3065
City Station
3079
External
WAN
Antenna
Cigarette Lighter
Power Input Cable
3077
3071
3069
PWS
Controller
3081
Multi-Dock
MLR
Link
3067
MLR Link
3075
3073
MLR
Module
Standard
VLD
Scanner

Fig. 29B


3113
3110
RADIO
TXD
RXD
RTS
CTS
DCD
MICROPROCESSOR
ADDRESS
INTERFACE
3112
3120
3121
3115

Fig. 30

Fig. 31



Fig. 32


MESSAGE TO SEND
3181
WAIT FOR IDLE SENSE SIGNAL
3183
IDLE SENSE SIGNAL RECEIVED ?
3185
NO
YES
EXECUTE BACK-OFF PROTOCOL
3180
3187
BACK-OFF ?
3189
YES
NO
ATTEMPT TRANSMIT
3191
COLLISION ?
3193
YES
NO
TRANSMIT MESSAGE
3195



Fig. 33a



Fig. 33b



Fig. 33c


3257
3261
3261
3269
3261
3261
3251
3253
3263
3265
3267
3271
3273
3275
3255
3259

Fig. 34


UPON RECEIVING A TRANSMISION FROM MICROLAN DEVICE
3311
3301
BEGIN
IDENTIFY A RANGE VALUE
3313
SUBSEQUENTLY, TRANSMIT RANGE VALUE TO THE MICROLAN DEVICE
3314
END
3303
UPON RECEIVING A RANGE VALUE
3321
BEGIN
3323
USING BATTERY PARAMETERS, IDENTIFY SUBSEQUENT DATA RATE (AND POWER LEVEL)
3325
SUBSEQUENTLY, TRANSMIT INDICATION OF IDENTIFIED DATA RATE (EXPLICIT/IMPLICIT)
END

Fig. 35

Fig. 36


UPON BINDING (AND PERIODICALLY)
3351
BEGIN
TRANSMIT INDICATION OF BATTERY PARAMETERS
3353
END
3355
UPON RECEIVING BATTERY PARAMETERS FROM A MICROLAN DEVICE
BEGIN
STORING THE BATTERY PARAMETERS
3357
END
3358
UPON RECEIVING A TRANSMISSION FROM MICROLAN DEVICE
BEGIN
3359
BASED ON RANGE AND USING STORED BATTERY PARAMETERS, IDENTIFY SUBSEQUENT DATA RATE (AND POWER LEVEL)
SUBSEQUENTLY, TRANSMIT INDICATION OF IDENTIFIED DATA RATE (& POWER LEVEL) TO MICROLAN DEVICE
3361
END


3511
3507
3505
3501
Transmitter Amplifier
Modulation Encoding
3513
3503
3515
Control Processor
3509
Frequency Generator
3523
Antenna Switching
3525
Power Source Control
Memory
Receiver RF Processing
Receiver Signal Processing
3522
3519
3517
3521

Figure 37


3509
f_{REF}
3603
Ref rence Oscillator
3605
÷ R
3609
Φ D
3611
LPF
f_{VCO}
3601
÷ N
3607

Figure 38



Figure 39



Figure 40


3759
3765
A/D
Converter
3769
3773
SIN
3751
3753
3755
Linear
Amp
fREF
Digital
Signal
Processor
3775
90°
3763
COS
3767
3771
A/D
Converter
3761

Figure 41


3823
MAC Select/Service Routines
3819
Common Mac Routines
3522
3811
Premises LAN MAC Routines
3813
Peripheral LAN MAC Routines
3815
Vehicular LAN MAC Routines
3817
WAN MAC Routines
3821
PHY Layer Control

Figure 42


Begin
3901
Need Additional Participation ?
Yes
3903
if required, register Sleep Mode With Other LANs
3905
Poll/Scan For The Additional LAN
3907
Has Additional LAN Been Located?
Yes
3909
Establish Participation
No
No
3911
Does A Participating LAN Need Servicing?
Yes
3913
if necessary, reestablish active participation status
3915
Participate As Needed Or Until Servicing Other LAN Overrides
3917
if necessary, establish Sleep Mode
No
3919
Need To Detach?
Yes
3921
if necessary, reestablish active participation status
3923
Explicit Or Implicitly Detach
No

Figure 43


Begin
3951
Poll/Scan For The Master LAN
3953
Has Master LAN Been Located ?
No
Yes
3955
Establish Participation With Master
3957
Continue Master LAN Participation Until Need For Slave Participation Overrides
3959
Is Slave LAN Participation Established ?
No
3961
Establish Slave Participation
Yes
3963
Continue Slave Participation As Needed Or Until Need To Service Master Overrides
3965
Is Slave LAN Participation Complete ?
No
3969
if necessary, Register Sleep Mode With Slave LAN
Yes
3967
Detach From Slave LAN

Figure 44


4501
4503
4505
4507
4509
4511
4521
4517
4525
4513
4523
4519
4515

Fig. 45


4621
4623
4625
4610
4609
4611
4619
4607
4613
4621
4615
4617
4605
4603
4601

Fig. 46a



Fig. 46b


4701
Await Incoming Transmission/Log Request
Time Out
Data/Code Request
Processing Request
Routing Request
Migration Request
4735
4723
4715
4703
4709
4725
4717
4711
Local Storage ?
Local Processing ?
Local Storage ?
4729
4713
Threshold ?
Retrieve Migr. Info
4731
Request Data/ Code
4733
4719
4705
Store Data/ Code
Perform Processing
Access Routing Table
4727
4721
4707
Retrieve Data/Code
Generate Response/ Results
Transmit/Route
Migr. Proc.
4737

Fig. 47a


BEGIN
4751
Next Code/ Data Entry
4753
Age Code/Data Entry
4755
Apply Cost Modifier
4757
Below Threshold ?
4761
Delete Stored Code/Data
4759
Last Entry ?
4763
Get Next Proc. Entry
4765
Age Proc. Entry
4767
Apply Cost Modifier
4769
Prog. Stored ?
4777
Possible ?
4771
Below Threshold ?
4779
Above Threshold ?
4773
Delete Stored Resources
4781
Retrieve Stored Resources
4775
End
Last Entry ?

Fig. 47b


4805
4809
4807
4803
LAN
Transceiver
Circuit
WAN
Transceiver
Circuit
4813
Comm. Processing
Memory
Migration
Processing
4815
Local Resources
Processing
Resource
Circuits/Devices
4811
4801

Fig. 48



Fig. 49a



Fig. 49b


4947
4941
4945
4944
4939
4945
4943
4929
4937
4933
4929
4949
4935
4951
4931

Fig. 49c


5001
LAN Transceiver Circuit
5007
Memory
5009
Image dB
Comm. Processing
Migration Processing
2–D Code Processing
Digital Signal Processing
5011
5005
5003

Fig. 50


BEGIN
Attempt Exact Identification
5101
5103
Success ?
Compare Received Image To Stored Images
5107
Identify Closest (Best) Match
5109
5111
Above Threshold ?
5105
Send 2–D Code Information
5113
Send Retry Message
End

Fig. 51a


BEGIN
Compare Received Image To Stored Images
5115
Identify Closest (Best) Match
5117
Above Threshold ?
5119
Perform Exact Identification
5123
Success ?
5125
Send 2-D Code Information
5121
Send Retry Message
5127
End

Fig. 51b


Main Category (Grocery)
Sub-Category (Beans)
Sub-Sub-Category (Lima)
Sub-Sub-Sub-Category (Del Monte)
Sub-Sub-Sub-Sub-Category (Can)
Sub-Sub-Sub-Sub-Sub-Category (10 oz.)
Further Categories of Other Information

Fig. 52

Grocery	Beans	Lima
Del Monte	Can	10 oz.

5303

Other Information

5301

Fig. 53


BEGIN
Retrieve Next Subcategory
5401
Compare with Stored Images
5403
Is Best Match W/In Accuracy Threshold ?
5405
Last Subcategory ?
5409
Indicate No Match Found
5407
Deliver 2-D Information
5411
End

Fig. 54


5501
5536
5515
5535
5517
5531
5529
5530
5537
5532
5519
5503
5525
5521
5509
5505
5541
5527
5507
5511
5513
5523
5539
5533
5522
5561
5565
5571
5579
5563
5577
5575
5573
5555
5557
5559
5581
5553
5551

Fig. 55a


5587
Assisting Access Device
5596
5597
5598
5589
Assisting Access Device
5590
5595
Non-Assisting Access Device (s)
5592
5599
5591
5593
5594
Source Device
Destination Device
5583
5585

Fig. 55b


5615
5613
5601
5609
Control Processing
5625
5627
5629
D/A Conversion
Queue Time Buffer
Modem/Fax Processing
5633
5611
5631
5607
Modem/Fax/ Voice Switching
5631
A/D Conversion
Output Buffer
5621
5623
5605
5603
5604

Fig. 56a


5601
5609
Control Processing
5625
D/A Conversion
5627
Queue Time Buffer
Modem/Fax Processing
5633
5651
Delay
5607
Modem/Fax/ Voice Switching
A/D Conversion
5653
Output Buffer
5621
5623

Fig. 56b



Fig. 57


5811
Queue Time Buffer
D/A Conversion
5813
5815
Control Processing
5801
Microphone/ Phone Processing
A/D Conversion
Output Buffer
5805
5809
5817
5819
5807

Fig. 58


5901
Packet Processing Idle State
Packet Route Request
5903
Call Setup Packet
5905
Call Voice Packet
Other Packet Types
5907
5911
5917
Phone Access ?
No
Yes
5919
Cost > ?
Yes
No
5921
Replace/Add Access Indicator
5923
Int. Route Entry ?
Yes
No
5925
Table Entry ?
No
Yes
5927
Add Internal Route Entry and Cost
5937
Direct Link ?
No
Yes
5941
Need Assistance ?
No
Yes
5943
Perform Assistance
5913
Branch to Service Routines
5939
Route Toward Destination
5929
Root Device ?
Yes
No
5931
Add Cost, Route Toward Root
5933
Create Reply Packet
5935
Add Cost, Route Toward Source

Fig. 59


Begin
6001
Phone Access ?
No
Yes
Offer Call Setup & Cost
6003
6005
Accepted ?
Yes
No
6009
Construct Call Request
6011
Send Toward Root
6013
Await Reply Packet
6015
Access Indicated ?
Yes
No
6017
Offer Call Setup & Cost Options
6019
Accepted ?
Yes
No
6007
Branch to Setup Routines
6021
Abort, Fail, End

Fig. 60


6101
Begin
6130
Offer Other Routes
6131
Route Selected ?
No
End
Yes
6103
Voice Mail ?
Yes
6105
Queue Up Voice Message
No
6107
Await Cost or Time Threshold
6109
Send Connect Packet
6111
Await Connect Response
6113
Path Available ?
No
Yes
6121
Adjust Queue Time Period
6123
Deliver Ring Signal
6115
Deliver Busy Signal
6117
Other Paths ?
Yes
No
6119
End
6125
Hang Detect ?
Yes
6127
End
No
6128
Pickup Detect ?
No
Yes
6129
Branch to Ongoing Call Processing

Fig. 61


6201
Await Ongoing Call Processing Event
Voice Delivery
6203
Error in Queue Time
6241
Local Hang
6231
Remote Hang
6235
Incoming Queue
6211
Outgoing Queue
6225
Voice Detect
6221
Queue Up Incoming
6205
Send Hang Up Message
6233
Deliver Click & Dial Tone
6237
Send Packet
6227
A/D Capture & Queue
6223
Adjust Queue Time
6243
End
6239
Ongoing ?
6213
No
Yes
Yes
Queue Time > Threshold ?
6215
No
Indicate Incoming Queue
6217
D/A Playback from Queue
6219

Fig. 62


6315
Internet Routing
Internet Provider
6305
Internet Provider/ Access Device
6333
Internet Routing
6307
6309
6301
6335
6303
6311
6327
6325
6321
6331
6323

Fig. 63